

# Stormy H Pro

## High pressure stationary models 15 bar

Some applications like truck tyres inflation for instance require high pressure. Sometime more than 12 bar, are necessary due to pressure drop on the network. Our 15 bar STORMY H PRO will fulfill such requirement.



Available in:

- Four horse powers from 4 to 10 HP
- Two sizes of vessel 300 or 500 litres (plus a vertical 270 litres variant)
- Star delta cubicle variant.









They include following features:

- Steel fan guard for protection
- Cast iron cylinders for improved cooling
- After cooler for reduced air temperature.

And starting from 5,5 HP units:

- Silenced inlet filter
- Inter cooler between the two stages
- Low rotation speed.

A wheelset and handle kit is available as an option for horizontal 300 and 500 litres tank.

TECHNICAL DATA														
TYPE														
		litre	bar	psi	l/min	cfm	HP	kW	rpm	V/Hz/Ph	L	W	H	Kg
300F4HYPRO	2 NS29S	300	15	218	367	13	4	3	1000	400/50/3	1640	500	995	170
300F5,5HYPRO	2 NS39	300	15	218	522	18,4	5,5	4	800	400/50/3	1640	500	1195	185
270F7,5HWPRO	2 NS39	270V	15	218	522	18,4	5,5	4	800	400/50/3	835	600	1950	180
500F7HYPRO	2 NS39	500	15	218	570	20,1	7,5	5,5	1000	400/50/3	1940	600	1375	230
500F7,5HYPRO	2 NS59S	500	15	218	760	26,8	7,5	5,5	600	400/50/3	1940	600	1375	245
500F10HYPRO	2 NS59S	500	15	218	941	33,3	10	7,5	750	400/50/3	1940	600	1375	250

(\* ) Star delta models available from 5,5 HP (+15 kg) except 270V models

270V = Vertical version

Other voltages available upon request